



ITALTOWER®
HEAVY DUTY LIGHTING TOWERS



OKAPI PRO02



Image for illustration purpose only.

Floodlight	Lumen	Light coverage
4x320W LED	179200 lm	9300 sq m



BAK Maskiner ApS

Karetmagervej 17A

7000 Fredericia, Danmark

Tlf. 32421300

www.bakmaskiner.dk

info@bakmaskiner.dk





Technical Specification

Rated frequency	50 Hz
Rated Voltage	230 V
Rated Power	3.5 Kw
Operating temperature	-40/+50
Sound Level	61 dB
Control unit	DeepSea L401
Auxiliary power	1 kVA

Engine

Model	Yanmar 2TNV70
Speed	1500 rpm
Coolant	Liquid
Cylinders	2
Emissions	Stage V

Alternator

Model	Linz Alumen
Rated outlet	3,5 kVA

Energy consumption

Fuel consumption	0,55 l/h
Tank	240 l
Fuel	Diesel
Running time	436 h

Galvanized mast

Height	8.5 m
Mast	Hydraulic
Rotation	355 °
Wind speed resistance	110 km/h

Canopy & Trailer

Trailer	Stationary
Tyres	/
Basement	Bunded base 110%
Stabilizers	4
Canopy	Powder coating paint

Optional

Optional included as standard	Dusk to dawn sensor with Autostart Grid/engine selector Battery isolator
-------------------------------	--

Shipment

Dimension	112x112x240 cm
Weight	850 kg
Truck	22 units
Container 40'	18 units

